

PS-3315

Entry level All In One POS system



MSR



CUSTOMER DISPLAY

PS-3315 terminal is a basic model that will meet the role of POS sales positions in any industry. PS-3315 has an Intel processor N2807 dual core. Thanks to "burst" of his speed even 2.16GHz! The new foldable stand at terminals allows you to adjust the terminal to the housing conditions and maintenance. Multi-configuration of the screen orientation for easy and quick work on the device.

The terminal is equipped with an infrared anti glare glass touch, making it sensitive to any pressure (touch) and impervious to water and sunlight. It allows you to work in glove.

Features:

- Intel N2807 processor, 1.58GHz/2.16GHz (Burst), 1M cache
- 15" TFT LCD - Infrared anti glare glass
- 1024 x 768 Resolution
- IR - touch
- 12V / 60W Power Supply

PS-3315 SPECIFICATIONS

Processor	Intel N2807 processor, 1.58GHz/2.16GHz (Burst), 1M cache
System Memory	DDR3L 1333MHz SO-DIMM x 1, Standard 4GB
Storage Device	2 x SATA Port (1 x SATA + 1 x mSATA) + 1 x eMMC connector, Standard 320GB HDD
Power Supply	12V / 60W
OS support	Windows 7 / POS Ready 7 / Windows Embedded 8.1 Industry / Linux per request

DISPLAY & TOUCH

LCD	15" TFT LCD - Antiglare glass
Resolution	1024 x 768
Touch	IR - touch

I/O & EXPANSION

Serial Port	4 x DB9, 5V/12V support on all COM ports
Parallel Port	1, via optional conversion cable
Standard	USB Port 5
Powered	USB Port Optional 24V x 1 + 12V x 3 via GEN8E base
LAN Port	10 / 100 / 1000 Mb x 1
Display Port	VGA x 1, 12V support
CR Port	1, control 2 CR via optional Y-cable
PS/2 Port	1, via optional conversation cable

