

HS-2510W

Small form factor All In One
POS



HS-2510W is the solution for the counter space problem. It takes the all-in-One concept to the extreme! The compact all-in-one design of HS-2510W frees more room for counter space, so that the store owner can display and promote more merchandizes to maximize sales opportunities.

Features:

- **Compact**

The compact footprint of HS-2510W makes itself adaptable to a wide range of counter styles and allows every inch of the work space usage to be optimized, thus creating maximum profit return for the store owners. This is what space saving is all about.

- **All-in-one**

As an "all-in-one" solution, HS-2510W touch-screen terminal integrates some of the most widely used peripherals in daily POS operation, such as 3" thermal printer, MSR, smart card reader, finger print sensor and 2nd customer display, and has the features and functionality to cater for applications in retail, hospitality, health care, banking and more, while offering uncompromising performance.

- **Aesthetics**

Dressed from head to toe in timeless black or white color, the only trend that never goes out of style, and with stylish touches added throughout, HS-2510W is not just a piece of machinery, it is an elegantly crafted piece of art that looks right at home in any store decoration.

HS-2510W SPECIFICATIONS

Processor	Intel J1900 Quad Core CPU, 2.00GHz up to 2.42GHz, 2M Cache
System Memory	DDR3L 1333MHz, SO-DIMM x 1,4GB Standard, upgradable upto 8GB
Storage Device	SATA Storage x 2 or eMMC x 1, 320GB Standard
Power Supply	12V DC power adaptor, 100W
OS support	Windows Embedded 8.1 Industry / Windows 7 / POSREADY 7 / Linux per request

DISPLAY & TOUCH

LCD	9.7" LCD panel
Resolution	1024 x 768
Touch	True-flat PCAP touch with 10"pts multi-touch support (IP65 on front panel)

I/O & EXPANSION

Serial Port	DB9 x 2 + RJ50 x 1 with 5V/12V support on COM1 / COM2 / COM3, RJ50 to DB9 cable optional
Parallel Port	Yes
Standard	4, 1 x USB 3.0/2.0 + 3 x USB 2.0
LAN Port	10 / 100 / 1000Mb x 1
CR Port	1, control 2CR
PS/2 Port	Yes
Audio	Line out
VGA Port	D-SUB, 15 pins, with 12V support
Mini-PCIe slot	Yes, for half size card

BUILT-IN DEVICE

Built-in MSR	Optional 3-track MSR (HID/VCOM selection)
Built-in Printer	3" thermal printer with auto cutter, 200mm/sec print speed
FPU	Optional finger print unit
Built-in WIFI	Optional mini-PCIe WIFI
Built-in RFID Reader	Optional RFID reader (HID/VCOM selection)
Built-in Smartcard Reader	Optional

PHYSICAL DIMENSION

Dimension (W x D x H in mm)	224.5 x 185 x 387
Weight (N. W. in kg)	4.2

ENVIRONMENTAL

Operating Condition	0°C - 40°C, 20%RH – 90%RH (Equipped with HDD) ; 0°C - 50°C20%RH – 90%RH (Equipped with SSD)
Storage Condition	(-20°C) – 70°C, 10%RH – 90%RH