## MT-4008



MT-4008W is the Windows based mobile POS terminal highlighted by an 8" tablet with the choice of a detachable pistol grip or a hand strap depending on the application. Its 1024 x 768 display resolution allows standard POS applications to be ported without modification. What's more, an optional dock station allows the device to have the features and functionality as an all-in-one POS.

## **Features:**

- 1024 x 768, 8" (7.85") LCD with PCAP 10 point multi touch panel
- Intel Atom Z3745D Quad Core CPU
- 2GB DDR3L memory
- 32GB eMMC storage + microSD
- 4800 mAh battery (tablet built-in), lasts upto 14 hrs with a pistol device
- Windows embedded 8.1 Industry
- Optional 3G and MSR attachment
- Pistol Grip with 5000mAh removable battery and optional 1D or 2D barcode scanner (MT-4008W/R only)
- Optional Dock Station with or without 3" WiFi thermal POS receipt printer, Serial ports, USB ports, LAN ports and CR ports built-in (DS-210 for MT-4008W/R & DS-310 for MT-4008W/H)
- Hand Strap cover (MT-4008W/H only)

MT-4008	SPECIFICATIONS
Processor	Intel® Bay Trail 1.33GHz Quad Core CPU
System Memory	2GB DDR3L
Storage Device	32 GB eMMC
Touch	Projected Capacitive Touch (10 point multi touch)
OS	Windows Embedded 8.1 Industry Pro
Display	8" LCD with 1024 x 768 resolution
Wireless Connectivity	WiFi 802.11 b/g/n; Bluetooth v4.0
Camera	5 Megapixel Rear-Facing Camera; 2 Megapixel Front Facing Camera
Speaker/ Mic	Yes
Sensors	Gyroscope
I/O	micro-SD, micro-USB
Battery	5000 mAh
Included Accessories	3 Track Encryption Capable MSR, Hand Strap
DOCKING STATION SPECIFICATIONS	
Printer	3" Thermal Printer, WiFi Interface
USB Port	3 x USB 2.0
LAN Port	Gigabit LAN
COM Port	2 x DB9 Serial
CR Port	1
OPTIONAL ITEMS	
Pistol Grip	With additional battery & option of 1D or 2D barcode scanner
Docking Station	With or without WiFi printer, 3 USB 2.0, 1 Lan, 2 DB9, 1 CR port
RB3000	Rechargable battery pack 5000mAH
CS-200	Charging rack with LED independent indication for 4 units maximum
CS-100	Battery charger for RB-3000 battery with independent LED indicator for 4 units maximum

